

規格變更通知

GT3 系列 多功能計時器, GT5Y 型/GT5P 型 小型計時器
GE1A 系列 電子計時器, RTE 系列 類比計時器

茲因 GT3 系列 多功能計時器、GT5Y 型/GT5P 型 小型計時器、GE1A 系列 電子計時器、RTE 系列 類比計時器部分規格有所變更，特此通知。

■ 實施期間

2024 年 7 月出貨起逐步實施。

※即使在實施日以前，因接單狀況而定，亦有可能提前以變更後產品出貨。

※依購買時期、購買數量而定，變更前後的產品可能同批出貨。



■ 對象製品及變更內容的概要

GT3 系列 多功能計時器：全機種

GT5Y 型/GT5P 型 小型計時器：全機種

GE1A 系列 電子計時器：全機種

RTE 系列 類比計時器：全機種

※包括以標準品為基礎的客製化規格品。





■ 變更內容

如下圖所示，製品的本體上將會追加用於追溯管理的 DataMatrix。另外，批號也會加入 IDEC 社內管理用的序號。






<GT3 系列 多功能計時器>

機種	變更前	變更後
GT3A GT3F GT3S GT3W	<p>UL Listed when used in combination with IDEC's SR2P-06 * type socket. (*-may be followed by suffix letter A, B, C or U) - Conductor Temperature Rating 60°C min. - Use No.14AWG to No.18AWG, Copper conductors only. - Terminal Torque 1.0 to 1.3 N·m. Use in Pollution Degree 2 environment.</p> <p>SEE INSTRUCTION SHEET FOR TIME RANGE. </p>	<p>UL Listed when used in combination with IDEC's SR2P-06 * type socket. (*-may be followed by suffix letter A, B, C or U) - Conductor Temperature Rating 60°C min. - Use No.14AWG to No.18AWG, Copper conductors only. - Terminal Torque 1.0 to 1.3 N·m. Use in Pollution Degree 2 environment.</p> <p>DataMatrix </p> <p>SEE INSTRUCTION SHEET FOR TIME RANGE. </p> <p>批號+序號 </p>











<GT5P 系列 小型計時器>

機種	變更前	變更後
GT5P	<p>IDEC ELECTRONIC TIMER SEE INSTRUCTION SHEET FOR TIME RANGE. I. Gr. B</p> <p>TYPE: GT5P-N1SA200 CONTACT RATING: 3A (RES.) 240VAC 5A (RES.) 120VAC/30VDC POWER: 200-240VAC (50/60Hz)</p>  <p>Use in Pollution Degree 2. MANUFACTURED IN TAIWAN</p> 	<p>IDEC ELECTRONIC TIMER TYPE: GT5P-N1SA200 CONTACT RATING: 3A (RES.) 240VAC 5A (RES.) 120VAC/30VDC POWER: 200-240VAC (50/60Hz)</p>  <p>DataMatrix</p> <p>批號+序號</p>  <p>***** MANUFACTURED IN TAIWAN</p>






<GT5Y 系列 小型計時器>

機種	變更前	變更後
GT5Y	 <p>POWER</p> <p>MODE: TTTT</p> <p>A</p> <p>B</p> <p>C</p> <p>D</p> <p>MANUFACTURED IN TAIWAN</p>  <p>IND.CONT.EQ. With IDEC's socket type SY4S-05*, SU4S-11L (* May suffix A, B, C, DF, DN or U)</p>	 <p>DataMatrix</p> <p>批號+序號</p>  <p>*****</p>  <p>IND.CONT.EQ. With IDEC's socket type SY4S-05*, SU4S-11L (* May suffix A, B, C, DF, DN or U)</p>

<GE1A 系列 電子計時器>

機種	變更前	變更後
GE1A	  <p>LISTED 68UK IND.CONT.EQ.</p>  <p>IDEC ELECTRONIC TIMER</p> <p>TYPE: GE1A-B10HA220</p>  <p>CONTACT RATING: 5A (RES.) 240VAC/24VDC POWER: 220-240VAC (50/60Hz)</p> <p>IDEC CORPORATION MANUFACTURED IN TAIWAN</p> 	  <p>LISTED 68UK IND.CONT.EQ.</p>  <p>IDEC ELECTRONIC TIMER</p> <p>TYPE: GE1A-B10HA220</p>  <p>CONTACT RATING: 5A (RES.) 240VAC/24VDC POWER: 220-240VAC (50/60Hz)</p> <p>IDEC CORPORATION MANUFACTURED IN TAIWAN</p> <p>DataMatrix</p> <p>批號+序號</p>  <p>*****</p>

<RTE 系列 電子計時器>

機種	變更前	變更後
GE1A	 <p>UL Listed when used in combination with IDEC's SR3P-05 * pin type socket. (*may be followed by suffix letter A, B, C or U) - Conductor Temperature Rating 60°C min. - Use Copper Conductors only, solid 12AWG max. (3.5mm² max.) - Terminal Torque 1.0 to 1.3 N·m. Use in Pollution Degree 2 environment.</p> <p>SEE INSTRUCTION SHEET FOR TIME RANGE.</p> 	 <p>UL Listed when used in combination with IDEC's SR3P-05 * pin type socket. (*may be followed by suffix letter A, B, C or U) - Conductor Temperature Rating 60°C min. - Use Copper Conductors only, solid 12AWG max. (3.5mm² max.) - Terminal Torque 1.0 to 1.3 N·m. Use in Pollution Degree 2 environment.</p> <p>DataMatrix</p> <p>SEE INSTRUCTION SHEET FOR TIME RANGE.</p>  <p>批號+序號</p> 

※上述以外的規格，以及型號、價格均無變更。

■ 識別標示

變更後的製品，其個裝盒的批號字尾將追加標示「B」。

識別標示期間：僅標示到 2025 年 1 月底製造品為止。

標示例：

