

材質變更通知

HG2G 型/HG3G 型 可程式人機介面

茲因隨著 HG2G 型/HG3G 型可程式人機介面的保護構造追加 Type 4X/13(鑲嵌至盤面時的正面)，因此製品上的標籤隨之變更，特此通知，詳情如下，敬請參考。

對象機種

對象機種(型號)	型號
HG2G 型 可程式人機介面	HG2G-5FT22TF-*
	HG2G-5ST22TF-*
	HG2G-5ST22VF-*
HG3G 型 可程式人機介面	HG3G-8JT22MF-*
	HG3G-8JT22TF-*
	HG3G-AJT22MF-*
	HG3G-AJT22TF-*



*:框體顏色(W:淺灰色、B:深灰色、S:銀色)(註)銀色僅 HG2G 系列對應。

※包含以以上機種為基礎機種的客製化製品。

















實施時期

自 2014 年 6 月製造品起陸續實施。

※依您的購買時期，數量而異，可能會發生變更前後製品混合存在的情形。

變更內容

因為保護構造追加 Type 4X/13(鑲嵌至盤面時的正面)，因此製品上的標籤隨之變更。

型號	變更前	變更後
HG2G -5FT	<p>IDEC</p> <p>TYPE: HG2G-5FT22TF-W S/N: 73Y25-00001 24V DC 19W, CLASS 2 MAX. TEMP.: 50°C TEMPERATURE CODE: T5 MADE IN JAPAN</p> <p>CLASS I DIV.2 GROUPS A, B, C, D. FOR USE ON A FLAT SURFACE OF A TYPE 1 ENCLOSURE. FOR CLASS 2 SOURCE ONLY.</p> <p>  IDEC CORPORATION</p>	<p>IDEC</p> <p>TYPE: HG2G-5FT22TF-W S/N: 73Y25-00001 24V DC 19W, CLASS 2 MAX. TEMP.: 50°C TEMPERATURE CODE: T5 MADE IN JAPAN</p> <p>CLASS I DIV.2 GROUPS A, B, C, D. FOR USE ON A FLAT SURFACE OF A TYPE 1, TYPE 4X INDOOR USE ONLY AND TYPE 13 ENCLOSURE. FOR CLASS 2 SOURCE ONLY.</p> <p>  IDEC CORPORATION</p>
HG2G -5ST	<p>IDEC</p> <p>MICRO/II™</p> <p>TYPE: HG2G-5ST22TF-W S/N: 73Y25-00001 12 to 24 V DC 8W, CLASS 2 MAX. TEMP.: 50°C TEMPERATURE CODE: T5 MADE IN JAPAN</p> <p>CLASS I DIV.2 GROUPS A, B, C, D. FOR USE ON A FLAT SURFACE OF A TYPE 1 ENCLOSURE. FOR CLASS 2 SOURCE ONLY.</p> <p>  IDEC CORPORATION</p>	<p>IDEC</p> <p>MICRO/II™</p> <p>TYPE: HG2G-5ST22TF-W S/N: 73Y25-00001 12 to 24 V DC 8W, CLASS 2 MAX. TEMP.: 50°C TEMPERATURE CODE: T5 MADE IN JAPAN</p> <p>CLASS I DIV.2 GROUPS A, B, C, D. FOR USE ON A FLAT SURFACE OF A TYPE 1, TYPE 4X INDOOR USE ONLY AND TYPE 13 ENCLOSURE. FOR CLASS 2 SOURCE ONLY. MADE IN JAPAN</p> <p>  IDEC CORPORATION</p>
HG3G -8	<p>IDEC MADE IN JAPAN</p> <p>TYPE: HG3G-8JT22TF-W S/N: 73Y25-00001 RATING: 24V DC 25W(max) MAX. TEMP.: 50°C TEMPERATURE CODE: T4A</p> <p>TIGHTENING TORQUE FOR MOUNTING: 0.5 to 0.6 Nm ONLY. FOR INSTALLATION CLASS I DIV.2 GROUPS A, B, C, D. FOR USE ON A FLAT SURFACE OF A TYPE 4X (INDOOR USE ONLY) ENCLOSURE. FOR CLASS 2 SOURCE ONLY USE MIN. 60°C WIRE, COPPER WIRE ONLY.</p> <p>  IDEC CORPORATION</p>	<p>IDEC MADE IN JAPAN</p> <p>TYPE: HG3G-8JT22TF-W S/N: 73Y25-00001 RATING: 24V DC 25W(max) MAX. TEMP.: 50°C TEMPERATURE CODE: T4A</p> <p>TIGHTENING TORQUE FOR MOUNTING: 0.5 to 0.6 Nm ONLY. FOR INSTALLATION CLASS I DIV.2 GROUPS A, B, C, D. FOR USE ON A FLAT SURFACE OF A TYPE 1, TYPE 4X INDOOR USE ONLY AND TYPE 13 ENCLOSURE. FOR CLASS 2 SOURCE ONLY USE MIN. 60°C WIRE, COPPER WIRE ONLY.</p> <p>  IDEC CORPORATION</p>
HG3G -A	<p>IDEC MADE IN JAPAN</p> <p>TYPE: HG3G-AJT22TF-W S/N: 73Y25-00001 RATING: 24V DC 25W(max) MAX. TEMP.: 50°C TEMPERATURE CODE: T4A</p> <p>TIGHTENING TORQUE FOR MOUNTING: 0.5 to 0.6 Nm ONLY. FOR INSTALLATION CLASS I DIV.2 GROUPS A, B, C, D. FOR USE ON A FLAT SURFACE OF A TYPE 4X (INDOOR USE ONLY) ENCLOSURE. FOR CLASS 2 SOURCE ONLY USE MIN. 60°C WIRE, COPPER WIRE ONLY.</p> <p>  IDEC CORPORATION</p>	<p>IDEC MADE IN JAPAN</p> <p>TYPE: HG3G-AJT22TF-W S/N: 73Y25-00001 RATING: 24V DC 25W(max) MAX. TEMP.: 50°C TEMPERATURE CODE: T4A</p> <p>TIGHTENING TORQUE FOR MOUNTING: 0.5 to 0.6 Nm ONLY. FOR INSTALLATION CLASS I DIV.2 GROUPS A, B, C, D. FOR USE ON A FLAT SURFACE OF A TYPE 1, TYPE 4X INDOOR USE ONLY AND TYPE 13 ENCLOSURE. FOR CLASS 2 SOURCE ONLY USE MIN. 60°C WIRE, COPPER WIRE ONLY.</p> <p>  IDEC CORPORATION</p>

其他

型號・價格均無變更。